

➔ OPTICAL MEDIA SHREDDER IDEAL 0201 OMD

INNOVATIVE HIGH PERFORMANCE SHREDDER FOR OPTICAL MEDIA ESPECIALLY DESIGNED FOR EFFICIENT DESTRUCTION OF CDs AND DVDs

High-quality cutting head with 2.2 x 4 mm particle size for high security needs according to German BSI - TL 03420 and North American NSA/CSS 04-02 requirements (particle size ≤ 10 mm²) | impressive shred speed guarantees high shred performance of up to 2,500 CDs or DVDs per hour (one by one feeding) | solid steel cutting shafts made of special hardened steel | suitable for all types of CDs and DVDs | "SPS" – (Safety Protection System) package: electronically controlled safety flap in the feed opening with specially designed feed slot to accept optical media and to prevent "fly back"; auto-matic reverse and power cut-off (to prevent jams); automatic stop if the collection bin is full; electronic door protection via a magnetic proximity switch; double motor protection; energy saving mode | multifunction control element "EASY_SWITCH" with integrated optical indicators for the operational status of the shredder | automatic start and stop via a photo cell | "ECC" - Electronic Capacity Control – indication of the used shred capacity during shredding process | automatic oil injection on the cutting shafts during shredding operation for constantly high shred performance | powerful 1600 watt motor for continuous operation | sturdy chain drive and dust-proof gear box housing | high-quality wooden cabinet, mobile on castors | anti-static collection bin (100 litres volume) made of an impact resistant plastic material | attractive colour combination: silver / dark grey | one year guarantee on all parts | quality "Made in Germany"

Power connection²: 230 V / 50 Hz / 1~, Dimensions (H x W x D): 1020 x 548 x 590 mm, Weight: approx. 104 kg



"ECC" CONTROL



"ECC" – Electronic Capacity

Control: for continuous feeding without creating paper jams the used sheet capacity is indicated during the shredding process.

AUTOMATIC OIL INJECTION



The automatic oil injection system lubricates the cutting shafts when shredding and guarantees a constantly high shred performance.

➔ IDEAL 0201 OMD

| | |
|-------------------------------|----------------------|
| Particle size | 2.2 x 4 mm |
| Approx. capacity ¹ | 2,500 pieces |
| Security standard | ≤ 10 mm ² |
| Feed opening | 310 / 130 mm |
| Motor capacity | 1600 Watt |

¹ CDs/DVDs per hour
² other voltages available



This machine is not suitable for shredding paper documents. The technical data is approximate. Subject to change 10/2009